



ALLIED INDUSTRIAL PRODUCTS

VALVES | AUTOMATION | FLANGES & FITTINGS

AN ISO 9001: 2015 CERTIFIED COMPANY



Allied
INDUSTRIAL
PRODUCTS



All Type of Industrial Valve, Pipe,
Pipe Fittings, Pneumatics,
Motorized Valve & Valve Automation

www.alliedvalves.com



GATE VALVES

API 600 | API 6D

Material Of Construction :
CI | CS | SS | WCB | WC6 | Wc9

End Connections

Screwed to BSP | BSPT | NPT |
Socket Weld | Butt Weld Ends |
Flanged Ends | Ring Type Joints (RTJ)

Pressure Rating :

ASA 125# | 150# | 300# |

Operation :

Manual | Gear

Size Range :

15mm to 600mm



BALL VALVES-FLOATING & TRUNNION MOUNTED

BS-5351 | BS-5159

Material Of Construction :

CI | CS | SS | A 105 | F304 | F316 | CF3

Seat & Seals :

PTFE | Reinforced PTFE | Buna-N |
Graphoil | Graphite

End Connections

Screwed to BSPT | NPT | Socket Weld |
Butt Weld with extended Nipple |
Flanged Ends | Butt Weld Ends

Pressure Rating :

ASA 150# | 300# | 800# |

Type :

Single Pc | Two Pc | Three Pc
900#

Operation :

Lever | Gear

Size Range :

6mm to 750mm



GLOBE VALVES

BS-1873 | ND-16 | ND-40

Material Of Construction :
CI | CS | SS

End Connections :

Screwed to BSP | BSPT | NPT |
Socket Weld | Butt Weld Ends |
Flanged Ends | Ring Type Joints (RTJ)

Pressure Rating :

ASA 125# | 150# | 300# |
| PN 16 | PN 40 | PN 64

Operation :

Manual | Gear

Size Range :

15mm to 600mm



BUTTERFLY VALVES

API 609 | BS-5155 | BS EN 593

Material Of Construction :

CI | DI | CS | SS

Seat & Seals :

Nitrile | Neoprene PTFE | Viton |
Hypalon | Silicon

End Connections

Wafer | Lug Ends

Pressure Rating :

ASA 125# | 150# | PN 10 | PN 16
PN 20 | PN 2.5

Type :

Centric Disc Design

Operation :

Lever | Gear

Size Range :

40mm to 500mm



NON RETURN VALVES

BS-1868 | API 6D

Material Of Construction :
CI | CS | SS

End Connections :

Screwed to BSP | BSPT | NPT |
Socket Weld | Butt Weld Ends |
Flanged Ends | Ring Type Joints (RTJ)

Pressure Rating :

ASA 125# | 150# | 300# |
| PN 16 |
PN 40 | PN 64

Type :

Swing | Lift-Up

Size Range :

15mm to 600mm



STRAINERS

Material Of Construction :

Cast Iron | Cast Steel | Stainless Steel

End Connections :

Flanged Ends | Screwed End

Type :

"Y" Type | "T" Type | Pot Type | Basket Type

Pressure Rating :

ASA 150# | 300# | PN 40

Size Range :

15mm to 800mm



FORGED STEEL VALVES-GATE, GLOBE, CHECK

API 602 | BS-5352

Material Of Construction :
ASTM A 105 | F304 | F304L | F316 |
F316L | F5 | F9 | F11 | F22

End Connections :
Socket Weld | Screwed | Butt Weld |
Flanged Ends |

Type :
"Y" Type Pattern

Pressure Rating :
ASA 800# | 1500# | 2500#

Size Range :
15mm to 50mm



DISC CHECK VALVE - NON SLAM

Material Of Construction :

Body : CF8 / CF8M
Disc : SS 304/ S.S. 316
Disc Seat : Metal to Metal / PTFE
Spring : Standard
Max. Oper. Press. : PN - 40
Max. OperTemp. : Upto 300°C

Size Range :
1/2" to 8"



WAFER | DUAL PLATE CHECK VALVES

API 6D | API 594

Material Of Construction :
CI | CS | SS | WC6 | WC9 | GM

End Connections
Wafer Type | Flanged End

Pressure Rating :
ASA 125# | 150# | PN 16

Size Range :
25mm to 1000mm



BALL FLOAT STEAM TRAP

Material Of Construction :

Moc : CI, CS
End Connection : Screwed / Flanged /
Socket Weld
Temperature : Upto 200°C
Media : Steam
Type : Vertical Type /
Horizontal Type

Size Range :
15mm to 50mm



KNIFE EDGE GATE VALVES

MS-SP-81

Material Of Construction :
CI | WCB | SS | WC6 | WC9

End Connections :
Wafer Type | Wafer Lugged |
Semi Lugged

Type :
BI - DIRECTIONAL | UNI - DIRECTIONAL

Pressure Rating :
PN 10 | PN 6 | ASA 150#

Size Range :
50mm to 600mm



TUBE GLASS

CARBON STEEL

Moc : EN 8 (150#)
Size : 15mm to 100mm

STAINLESS STEEL

Moc : SS 304 / 316 (150#)
Size : 15mm to 150mm

INVESTMENT CASTING

Moc : CF8 / CF8M (150#)
Size : 25mm to 150mm



2/2 WAY PNEUMATIC ANGLE TYPE ON/OFF CONTROL VALVE

Material Of Construction :

Type : Normally Close / Open
Body : CF8 / CF8M
Pneu. Press. : 3.5 to 7 Bar
Working Press. : Upto 16 Bar
Working Temp. : 180°C
Ends : Screwed / Flanged
Media : Air, Water, Oil, Gas,
Steam & Chemicals

Size Range :

1/2" to 3"



STAINLESS STEEL - GATE | GLOBE | NRV

SCREWED END

Material Of Construction :

SS 304 | SS 316 | SS 304L | SS 316L

End Connections

Screwed to BSP | BSPT | NPT |
Socketweld to ASME B 16.11

Pressure Rating :

Body : 425 Psig (30 Kg/Cm²)
Seat : 300 Psig (21 Kg/Cm²)

Size Range :

15mm to 50mm



GUN METAL | BRONZE VALVES

- Gate Valve as per IS 778 CL-I
- Globe Valve as per IS 778 CL-I
- Horizontal Non Return Valve as per IS 778 CL-I
- Steam Stop Valve



FLANGES & FITTINGS

IBR APPROVED

Material Of Construction :

MS | A105 | SS 304 | SS 316 | SS 304L | SS 316L

Rating :

ASA 150# to 2500# | ND-40 |
BS 10 TABLE E | D | F | K | J

Type :

SORF | Blind | WNRF Etc.

Size Range :

15mm to 2000mm

FITTINGS : IBR APPROVED

- Carbon Steel (MS) Seamless Bends
- Long Radius
- MS (Carbon Steel) Elbows
- Long Radius
- MS (Carbon Steel) Concentric Reducers



www.alliedvalves.com



- 👤 Mr. Nizamuddin Bastawala
(B.com, M.com and LLB)
- ☎ +91 95103 24661 / 79847 42324
- ✉ sales@alliedvalves.com
- ✉ levelvalves@gmail.com

Registered &
Corporate Office :
3237, Bearing Bazar,
Kadikui Corner, Relief Road,
Ahmedabad-380001 (Gujarat)